



ENGINE PAINT SEALING LOCATIONS

DE CO

	JR/SR STOCK	MOD	“B”	“A”	HALF
Carb/Air Filter Adapter * NOTE: Air filter must be removed to properly seal the mounting bolt					
Mounting Bolt *	YES	NO	NO	NO	NO
Carb to Manifold	YES	NO	NO	NO	NO
Exhaust Restrictor Bolt	(Jr Stock Only) YES	NO	NO	NO	NO
Manifold to Block	YES	NO	NO	NO	NO
Head Bolt	YES	YES	YES	YES	YES
Gearbox to Block	YES	YES	YES	YES	NO
Flywheel Nut	YES	YES	YES	YES	YES
Shroud Bolt	YES	YES	YES	YES	NO
Paint Qualifying # on Frame.	YES	YES	YES	YES	YES
Paint Qualifying # on Engine.	YES	YES	YES	YES	YES
Total # of Points	10	6	6	6	4

HONDA

1. Air Filter Adapter Mounting Bolt (Air filter must be removed to properly seal the mounting bolt)
2. Carb Bowl Bolt
3. Carb Bowl Drain Bolt
4. Rocker Cover Bolt
5. Gear Box Bolt at Gear Box Cover
6. Side Cover to Block Bolt
7. Fan Shroud Bolt
8. Flywheel Nut
9. Exhaust Flange
10. Paint Qualifying # on Frame
11. Paint Qualifying # on Engine

PLEASE CHECK THE QMA WEB SITE FREQUENTLY FOR TECHNICAL NEWS AND UPDATES TO ALL DOCUMENTS
QMA National Tech Director Jerry Mostek