



Animal

CAMSHAFT PROFILE SHEET

Name Driver/Handler _____ Date _____

Serial Number _____

Event: _____ Tech Personnel _____

Intake Degrees

0.005 55 TO 65 BTDC _____

0.020 12 TO 19 BTDC _____

0.050 0 TO 5 ATDC _____

0.100 17 TO 21 ATDC _____

0.150 32 TO 38 ATDC _____

0.200 53 TO 58 ATDC _____

0.225 66 TO 72 ATDC _____

0.250 88 TO 93.5 ATDC _____

0.258 MAX (104 TO 107 CL.)

0.250 117 TO 123 ATDC _____

0.225 141 TO 145 Split ATDC _____

0.200 154 TO 159 ATDC _____

Exhaust Degrees

0.005 277 TO 284 BTDC _____

0.020 236 TO 241 BTDC _____

0.050 219 TO 224 BTDC _____

0.100 202 TO 206 BTDC _____

0.150 185 TO 190 BTDC _____

0.200 165 TO 171 BTDC _____

0.225 152 TO 156 Split BTDC _____

0.250 129 TO 135 BTDC _____

0.259 MAX. (113 TO 116 CL.)

0.250 92 TO 98 1/2 BTDC _____

0.225 71 TO 76 Split BTDC _____

0.200 58 TO 62.5 BTDC _____

0.150 174 TO 179 ATDC _____

0.150 38 TO 43 BTDC _____

0.100 191 TO 196 ATDC _____

0.100 21.5 TO 26 BTDC _____

0.050 208 TO 213 ATDC _____

0.050 4.5 TO 9 ATDC _____

0.020 225 TO 232 BTDC _____

0.020 7 TO 13 ATDC _____

0.005 268 TO 276.5 BTDC _____

0.005 47 TO 59 ATDC _____

NOTES: