



**HONDA GX 160 UT-2 (ONLY)**  
**CAMSHAFT PROFILE SHEET**

Name Driver/Handler \_\_\_\_\_ Date \_\_\_\_\_

GX160- UT 2 (ONLY)  
(Circle)

Serial Number \_\_\_\_\_

Division: Lt. Hvy  
(Circle)

Class: H160  
(Circle)

Event: \_\_\_\_\_ Tech Personnel \_\_\_\_\_

**Intake Degrees**

**Exhaust Degrees**

0.050" 4 - 8 ATDC \_\_\_\_\_ 0.050" 208 - 212 BTDC \_\_\_\_\_

0.100" 22 - 27 ATDC \_\_\_\_\_ 0.100" 191 - 195 BTDC \_\_\_\_\_

0.150" 42 - 46 1/2 ATDC \_\_\_\_\_ 0.150" 172 - 176 BTDC \_\_\_\_\_

**0.180" (SPLIT) \_\_\_\_\_ 0.180" (SPLIT) \_\_\_\_\_**

0.200" 71 - 75 ATDC \_\_\_\_\_ 0.200" 145 - 149 BTDC \_\_\_\_\_

**MAX LIFT 0.227" \_\_\_\_\_ MAX LIFT 0.229" \_\_\_\_\_**

0.200" 143 1/2 - 147 ATDC \_\_\_\_\_ 0.200" 70 - 74 BTDC \_\_\_\_\_

**0.180" (SPLIT) \_\_\_\_\_ 0.180" (SPLIT) \_\_\_\_\_**

0.150" 172 - 175 1/2 ATDC \_\_\_\_\_ 0.150" 41 1/2 - 45 BTDC \_\_\_\_\_

0.100" 192 1/2 - 195 1/2 ATDC \_\_\_\_\_ 0.100" 22 - 25 BTDC \_\_\_\_\_

0.050" 210.5 1/2 - 214 ATDC \_\_\_\_\_ 0.050" 4 1/2 - 8 1/2 BTDC \_\_\_\_\_

NOTES: