

2023 Safety & Registration Sheet

Transponder No.

Pill Draw No.

REGISTRATION

Driver's Name: _____		DIVISION	CLASS
Date of Birth: _____	Age: _____	Advanced	Novice World Formula
Address: _____	Region: _____	Junior	Honda Half
QMA Club: _____	Driver Weight: _____	Senior	Animal
Driver ID No.: _____		Light	MOD
Handler Cell: _____		Heavy	160
			B

CAR SAFETY CHECK

Information must be completed prior to the safety inspection.

<p>Roll Cage _____ Min. 1" to helmet, Down-tube design, No additions</p> <p>Nerf Bar/Bumpers _____ Minimum 6/32 bolt, 2" minimum, socket head type</p> <p>Shoulder Bar _____ Minimum 6/32 bolt at stud of clamp, socket head type</p> <p>Steering _____ No over center, no binding</p> <p>Steering Wheel _____ 1" thick pad, 2" diameter pad, min.</p> <p>Ignition System _____ All securely fastened, up for On, Top switch for Novice</p> <p>Seat/Shoulder/Belts _____ Belt 5 Point (4 yr replacement, SFI 16.1 driver over 100 lb & 16.1 or 16.2 driver under 100 lb). Any seat belt mounting location must ensure belts are NOT exposed to physical damage outside the cockpit.</p> <p>Date: _____</p> <p>Belly Pan _____ Minimum gauge 0.040 AL, No open holes</p> <p>Weight _____ No loose weights</p> <p>Brakes _____ Full pedal or heel stop & metallic shielded brake line</p> <p>Oil Catch Can _____ Engine compartment</p> <p>Sticker _____ QMA _____ Spec. Tire _____ On right exterior side of car</p>	<p>Axles/Hubs _____ Axles not past wheels, No Carbon Fiber</p> <p>Tires/Wheels _____ Three lug nuts minimum</p> <p>Body Height 28" (max) _____ No sharp edges</p> <p>Side Panels 22" (max) _____ Must extend 2" past center line of flywheel & Eng gear hub 2" hole for access to flywheel nut</p> <p>Side Panels & Visor _____ Supported and securely fastened</p> <p>Enclosed Nose Section _____</p> <p>Tail Cone _____ Below top of bumper</p> <p>Fire Wall _____ Minimum gauge 0.048 AL, No open holes</p> <p>Fuel System _____ Minimum positive stop clamp</p> <p>Fuel Line _____ Fire Resistant sleeve or SS Braid</p> <p>Fuel Cap _____ Tight Fitting, All seals required</p> <p>Exhaust System _____ No leaks & tight muffler</p> <p>Throttle Cable _____ No Binding</p>
---	---

DRIVER'S EQUIPMENT

<p>Helmet _____ SNELL SA2015, SFI24.1 or CMR2016 + SFI 3.3 Head Sock</p> <p>Face Shield _____ No Cracks</p> <p>Jacket/Pants or Suite _____ SFI 3.2A/1 OR 3.4/5 minimum</p> <p>Head & Neck Restraint (recommended) _____ SFI 38.1, 5 Year Recertification</p>	<p>Arm Restraints _____ Worn close to wrists, not above elbow</p> <p>Neck Collar _____ SFI 3.3</p> <p>Gloves _____ SFI3.3/5 2-layer</p> <p>Shoes _____ Completely cover feet, flat bottom</p>
--	---

General Safety Condition: _____

Safety Director's Signature: _____

I agree to assume all responsibility at this event and to abide by all QMA rules and procedures.

Owner/Handler's Name: _____

Owner/Handler's Signature: _____