

# 2024 Safety & Registration Sheet

Transponder No.

Pill Draw No.

## REGISTRATION

<b>Driver's Name:</b> _____		<b><u>DIVISION</u></b>	<b><u>CLASS</u></b>	
<b>Date of Birth:</b> _____	<b>Age:</b> _____	<b>Junior</b>	<b>Novice</b>	<b>MOD WF</b>
<b>Address:</b> _____	<b>Region:</b> _____	<b>Advanced</b>	<b>Honda</b>	<b>World Formula</b>
<b>QMA Club:</b> _____	<b>Driver Weight:</b> _____	<b>Senior</b>	<b>Animal</b>	<b>Half</b>
<b>Driver ID No.:</b> _____		<b>Light</b>	<b>160</b>	
<b>Handler Cell:</b> _____		<b>Heavy</b>		

## CAR SAFETY CHECK

Information must be completed prior to the safety inspection.

<p><b>Roll Cage</b> _____ Min. 1" to helmet, Down-tube design, No additions</p> <p><b>Nerf Bar/Bumpers</b> _____ Minimum 6/32 bolt, 2" minimum, socket head type</p> <p><b>Shoulder Bar</b> _____ Minimum 6/32 bolt at stud of clamp, socket head type</p> <p><b>Steering</b> _____ No over center, no binding</p> <p><b>Steering Wheel</b> _____ 1" thick pad, 2" diameter pad, min.</p> <p><b>Ignition System</b> _____ All securely fastened, up for On, Top switch for Novice</p> <p><b>Seat/Shoulder/Belts</b> _____ Belt 5 Point (4 yr replacement, SFI 16.1 driver over 100 lb &amp; 16.1 or 16.2 driver under 100 lb). Any seat belt mounting location must ensure belts are NOT exposed to physical damage outside the cockpit.</p> <p>Date: _____</p> <p><b>Belly Pan</b> _____ Minimum gauge 0.040 AL, No open holes</p> <p><b>Weight</b> _____ No loose weights</p> <p><b>Brakes</b> _____ Full pedal or heel stop &amp; metallic shielded brake line</p> <p><b>Oil Catch Can</b> _____ Engine compartment</p> <p><b>Sticker</b> _____ <b>QMA</b> _____ <b>Spec. Tire</b> _____ On right exterior side of car</p>	<p><b>Axles/Hubs</b> _____ Axles not past wheels, No Carbon Fiber</p> <p><b>Tires/Wheels</b> _____ Three lug nuts minimum</p> <p><b>Body Height 28" (max)</b> _____ No sharp edges</p> <p><b>Side Panels 22" (max)</b> _____ Must extend 2" past center line of flywheel &amp; Eng gear hub 2" hole for access to flywheel nut</p> <p><b>Side Panels &amp; Visor</b> _____ Supported and securely fastened</p> <p><b>Enclosed Nose Section</b> _____</p> <p><b>Tail Cone</b> _____ Below top of bumper</p> <p><b>Fire Wall</b> _____ Minimum gauge 0.048 AL, No open holes</p> <p><b>Fuel System</b> _____ Minimum positive stop clamp</p> <p><b>Fuel Line</b> _____ Fire Resistant sleeve or SS Braid</p> <p><b>Fuel Cap</b> _____ Tight Fitting, All seals required</p> <p><b>Exhaust System</b> _____ No leaks &amp; tight muffler</p> <p><b>Throttle Cable</b> _____ No Binding</p>
---	---

## DRIVER'S EQUIPMENT

<p><b>Helmet</b> _____ SNELL SA2015, SFI24.1 or CMR2016 + SFI 3.3 Head Sock</p> <p><b>Face Shield</b> _____ No Cracks</p> <p><b>Jacket/Pants or Suite</b> _____ SFI 3.2A/1 OR 3.4/5 minimum</p> <p><b>Head &amp; Neck Restraint (recommended)</b> _____ SFI 38.1, 5 Year Recertification</p>	<p><b>Arm Restraints</b> _____ Worn close to wrists, not above elbow</p> <p><b>Neck Collar</b> _____ SFI 3.3</p> <p><b>Gloves</b> _____ SFI3.3/5 2-layer</p> <p><b>Shoes</b> _____ Completely cover feet, flat bottom</p>
--	---

**General Safety Condition:** \_\_\_\_\_

**Safety Director's Signature:** \_\_\_\_\_

**I agree to assume all responsibility at this event and to abide by all QMA rules and procedures.**

**Owner/Handler's Name:** \_\_\_\_\_

**Owner/Handler's Signature:** \_\_\_\_\_