



**Animal**

**CAMSHAFT PROFILE SHEET**

Name Driver/Handler \_\_\_\_\_ Date \_\_\_\_\_

Serial Number \_\_\_\_\_

Event: \_\_\_\_\_ Tech Personnel \_\_\_\_\_

**Intake Degrees**

**Exhaust Degrees**

0.005 55 TO 65 BTDC \_\_\_\_\_

0.005 277 TO 284 BTDC \_\_\_\_\_

0.020 12 TO 19 BTDC \_\_\_\_\_

0.020 236 TO 241 BTDC \_\_\_\_\_

0.050 0 TO 5 ATDC \_\_\_\_\_

0.050 219 TO 224 BTDC \_\_\_\_\_

0.100 17 TO 21 ATDC \_\_\_\_\_

0.100 202 TO 206 BTDC \_\_\_\_\_

0.150 32 TO 38 ATDC \_\_\_\_\_

0.150 185 TO 190 BTDC \_\_\_\_\_

0.200 53 TO 58 ATDC \_\_\_\_\_

0.200 165 TO 171 BTDC \_\_\_\_\_

0.225 66 TO 72 ATDC \_\_\_\_\_

0.225 152 TO 156 Split BTDC \_\_\_\_\_

0.259 MAX (104 TO 107 CL.)

0.259 MAX. (113 TO 116 CL.)

0.225 141 TO 145 Split ATDC \_\_\_\_\_

0.225 71 TO 76 Split BTDC \_\_\_\_\_

0.200 154 TO 159 ATDC \_\_\_\_\_

0.200 58 TO 62.5 BTDC \_\_\_\_\_

0.150 174 TO 179 ATDC \_\_\_\_\_

0.150 38 TO 43 BTDC \_\_\_\_\_

0.100 191 TO 196 ATDC \_\_\_\_\_

0.100 21.5 TO 26 BTDC \_\_\_\_\_

0.050 208 TO 213 ATDC \_\_\_\_\_

0.050 4.5 TO 9 ATDC \_\_\_\_\_

0.020 225 TO 232 BTDC \_\_\_\_\_

0.020 7 TO 13 ATDC \_\_\_\_\_

0.005 268 TO 276.5 BTDC \_\_\_\_\_

0.005 47 TO 59 ATDC \_\_\_\_\_

---

NOTES: