

2025 Safety & Registration Sheet

Transponder No. _____

Pill Draw No. _____

REGISTRATION

Driver's Name: _____
 Date of Birth: _____
 Address: _____
 QMA Club: _____
 Membership #: _____
 Handler Cell: _____

Age: _____
 Driver Weight: _____

<u>DIVISION</u>	<u>CLASS</u>	
Junior	Novice	MOD WF
Advanced	Honda	World Formula
Senior	Animal	Half
Light	160	
Heavy		

CAR SAFETY CHECK

Information must be completed prior to the safety inspection.

Roll Cage _____
Min. 1" to helmet, Down-tube design, No additions

Nerf Bar/Bumpers _____
Minimum 6/32 bolt, 2" minimum, socket head type

Shoulder Bar _____
Minimum 6/32 bolt at stud of clamp, socket head type

Steering _____
No over center, no binding

Steering Wheel _____
1" thick pad, 2" diameter pad, min.

Ignition System _____
All securely fastened, up for On, Top switch for Novice

Seat/Shoulder/Belts _____
Belt 5 Point (4 yr replacement, SFI 16.1 driver over 100 lb & 16.1 or 16.2 driver under 100 lb). Any seat belt mounting location must ensure belts are NOT exposed to physical damage outside the cockpit.

Date: _____

Belly Pan _____
Minimum gauge 0.040 AL, No open holes

Weight _____
No loose weights. Weights are neon or white tape covered and bolted with 1.5" minimum fender washer

Brakes _____
Full pedal or heel stop & metallic shielded brake line

Oil Catch Can _____
Engine compartment

Sticker _____ **QMA** _____ **Spec.** _____
On right exterior side of car **Tire** _____

Helmet _____
SNELL SA2015, SFI24.1 or CMR2016 + SFI 3.3 Head Sock

Face Shield _____
No Cracks

Jacket/Pants or Suite _____
SFI 3.2A/1 OR 3.4/5 minimum

Head & Neck Restraint (recommended) _____
SFI 38.1, 5 Year Recertification

Axles/Hubs _____
Axles not past wheels, No Carbon Fiber

Tires/Wheels _____
Three lug nuts minimum

Body Height 28" (max) _____
No sharp edges

Side Panels 22" (max) _____
Must extend 2" past center line of flywheel & Eng gear hub
 2" hole for access to flywheel nut

Side Panels & Visor _____
Supported and securely fastened

Enclosed Nose Section _____

Tail Cone _____
Below top of bumper

Fire Wall _____
Minimum gauge 0.048 AL, No open holes

Fuel System _____
Minimum positive stop clamp

Fuel Line _____
Fire Resistant sleeve or SS Braid

Fuel Cap _____
Tight Fitting, All seals required

Exhaust System _____
No leaks & tight muffler

Throttle Cable _____
No Binding

DRIVER'S EQUIPMENT

Arm Restraints _____
Worn close to wrists, not above elbow

Neck Collar (mandatory) _____
Nomex or equivalent (required) & SFI tag (required)

Gloves _____
SFI3.3/5 2-layer

Shoes _____
Completely cover feet, flat bottom

General Safety Condition: _____

Safety Director's Signature: _____

I agree to assume all responsibility at this event and to abide by all QMA rules and procedures.

Owner/Handler's Name: _____

Owner/Handler's Signature: _____