

2026 Safety & Registration Sheet

Transponder No.

Pill Draw No.

REGISTRATION

Driver's Name: _____		<u>DIVISION</u>	<u>CLASS</u>	
Date of Birth: _____	Age: _____	Junior	Novice	MOD WF
Address: _____		Advanced	Honda	World Formula
QMA Club: _____	Driver Weight	Senior	Animal	Half
Membership #: _____	Over 100# Yes / No	Light	160	
Handler Cell: _____		Heavy		

CAR SAFETY CHECK

<p>Roll Cage _____ Min. 1" to helmet, Down-tube design, No additions</p> <p>Shoulder Bar _____ Minimum 6/32 bolt at stud of clamp, Socket head type</p> <p>Steering _____ No over center, No binding</p> <p>Steering wheel _____ 1" thick pad, 2" diameter pad minimum</p> <p>Ignition System _____ All securely fastened, Up for on, Top switch for Novice</p> <p>Brakes _____ Full pedal or heel stop & metallic shielded brake line</p> <p>Throttle Cable _____ No Binding, Two throttle springs required</p> <p>Oil Catch Can _____ Must be located in engine compartment</p> <p>Seat / Shoulder Belts _____ Belt 5 point (4yr replacement, SFI 16.1 if driver over 100# Any seat belt mounting location must ensure belts are NOT exposed to physical damage outside the cockpit. Circle 16.1 / 16.2</p> <p>Belly pan _____ Minimum gauge 0.040 AL, No open holes</p> <p>Weight _____ No loose weights, Weights must be NEON or White tape covered and bolted with 1.5" minimum fender washer</p> <p>Enclosed Nose Section _____</p>		<p>Fire Wall _____ Minimum gauge 0.048 AL, No open holes</p> <p>Fuel system _____ Minimum positive stop clamp</p> <p>Fuel Line _____ Fire Resistant sleeve or SS Braid</p> <p>Fuel Cap _____ Tight fitting, All seals required</p> <p>Exhaust System _____ No leaks & tight muffler</p> <p>Tail Cone _____ Below top of bumper</p> <p>Sticker _____ Required on right side of car QMA _____ Vega _____</p> <p>Axle / Hubs _____ Axles not past wheels, No carbon fiber</p> <p>Tires / Wheels _____ Three lug nuts minimum</p> <p>Body Height 28" (Max) _____ No sharp edges</p> <p>Side Panels 22" (Max) _____ Must extend 2" past centerline of flywheel & Eng gear hub 2" Hole for access to flywheel nut</p> <p>Side panels & Visor _____ Supported and securely fastened</p> <p>Nerf Bar/ Bumpers _____ Minimum 6/32" bolt, 2 minimum, socket head type</p>
--	--	--

Driver's Equipment

<p>Helmet _____ Snell SA2020 or newer or SFI 24.1/2020 or newer</p> <p>Face shield _____ No cracks, No tinted shields after dark</p> <p>Head Sock _____ Required in WFM and Half classes, SFI 3.3</p> <p>Jacket / Pants or Suit _____ SFI 3.2A/1 or 3.4/5 minimum</p> <p>Head & Neck Restraint (Recommended) _____ SFI 38.1, 5 Year Recertification</p>		<p>Arm Restraints _____ Worn close to wrists, not above elbow</p> <p>Neck Collar (Mandatory) _____ Nomex or equivalent (required) & SFI tag (required)</p> <p>Gloves _____ SFI 3.3/5 2-layer</p> <p>Shoes _____ Completely cover feet, Flat Bottom, No holes, No Crocs</p>
--	--	--

General Safety Condition: _____

I agree to assume all responsibility at this event and to abide by all QMA rules and procedures.

Owner / Handler's Name: _____

Safety Director's Signature : _____

Owner / Handler's Signature: _____